



- **Stainless steel spiral hose** used as steel conduit is a general purpose **high quality connecting hose**.
Made of AISI 304L stainless steel material.
- Tin-plated copper wire mesh is **provided by wrapping it in a steel conduit**.
- Provides high compressive strength.
- It is produced in **10 different diameters from 10,7 mm to 62,4 mm**.

AC-4400 EMI Cable Shielding With Metal Conduit Cu/Sn*						
Product Code	Steel Conduit Inner Diameter (mm)	Steel Conduit Outer Diameter (mm)	Knitted Outer Diameter (mm)	Tolerance (mm)	Copper Wire Diameter (mm)	Minimum Bending Diameter Static r _{min} (mm)
AC-4411	6,2	9,6	10,7	± 0,2	0,127	25
AC-4414	8,2	12,2	13,7	± 0,2	0,127	34
AC-4416	10,2	14,2	15,6	± 0,3	0,127	38
AC-4418	12,2	16,3	17,8	± 0,3	0,127	44
AC-4423	16,2	21,6	22,8	± 0,3	0,127	48
AC-4429	20,2	26,9	28,5	± 0,3	0,200	69
AC-4434	25,3	32,1	33,8	± 0,4	0,200	84
AC-4444	32,2	41,1	43,1	± 0,4	0,200	104
AC-4453	40,1	49,7	52,1	± 0,4	0,200	129
AC-4463	50,2	60,2	62,4	± 0,5	0,200	160

* With tin-plated copper wire.

